



SINOTRADE
GLOBAL LTD H.K.



FIRE HOSE REEL

Code: DL-R01

- ❖ Manual swing
- ❖ 1" x30M, 1" x25M, 3/4" x30M
- ❖ Working pressure: 12Bar (Max. 15Bar)
- ❖ High performance fire hose complies with EN694
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system
- ❖ Certification: EN671:1-2001



Code: DL-R02

- ❖ Manual swing (Central Union)
- ❖ 1" x30M, 3/4" x30M
- ❖ Working pressure: 12Bar (Max.15Bar)
- ❖ EN694 approved reinforced fire hose, red/black
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system
- ❖ Standard: EN671:1-2001

Code: DL-R03

- ❖ Manual Fixed
- ❖ 3/4" x30M, 1" x30M
- ❖ Working pressure: 12Bar
- ❖ High performance fire hose comply with EN694
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system



Code: DL-R04

- ❖ Manual Swing
- ❖ Steel arm with brass core
- ❖ DN25 x30M, DN33 x30M
- ❖ Working pressure: 12Bar
- ❖ EN694 approved reinforced fire hose, red/black
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system



SINO TRADE
GLOBAL LTD H.K.



Code: DL-R05

- ❖ Manual Swing
- ❖ DN25 x30M, DN33 x30M
- ❖ Working pressure: 12Bar
- ❖ EN694 approved reinforced fire hose, red/black
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system

Code: DL-R06

- ❖ Manual Fixed
- ❖ South African model 19mmx30M
- ❖ Working pressure: 12Bar
- ❖ EN694 approved reinforced fire hose, red/black
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system



Code: DL-R07

- ❖ Manual Fixed
- ❖ DN25 x30M, DN33 x30M
- ❖ Working pressure: 12Bar
- ❖ EN694 approved reinforced fire hose, red/black
- ❖ 100% Hydraulic tested
- ❖ Production under ISO9001 quality system

Code: DL-R08

- ❖ Reel for Jacket lining hose
- ❖ 1½ " x30M, 2½ " x30M
- ❖ Production under ISO9001 quality system

